

SPECIFICATIONS:

1. ELECTRICAL CHARACTERISTICS

- 1-1. CURRENT RATING: 0.5 AMP
- 1-2. VOLTAGE RATING: 40 V
- 1-3. CONTACT RESISTANCE: 30MILLIOHMS MAX
- 1-4. INSULATION RESISTANCE:100M MIN.@500V DC
- 1-5. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE

2. MECHANICAL CHARACTERISTICS:

- 2-1. INSERTION FORCE : 4.5KGF MAX.
- 2-2. WITHDRAWING FORCE : 1KGF ~ 4KGF.

3. LIFE TEST: 10000 CYCLES

4. OPERATING TEMPERATURE: -25°C TO +85°C

5. PART NO. DESCRIPTION:

KHD17 - X X X XX X-01

SHELL MATERIAL:
1:SUS304

SHELL PLATED:
1:鍍鎳

TERMINAL MATERIAL:
1:COPPER ALLOY

HOUSING COLOR:
B:BLACK (LCP)

CONTACTS PLATED:
01:半金錫1u"
02:半金錫15u"
03:半金錫30u"

※ SIGN "X" IS IMPORTANCE DIMENSION

3	SHELL	1	SUS304 T=0.50	NI PLATED
2	TERMINAL	19	COPPER ALLOY T=0.20	AU/TIN PLATED
1	HOUSING	1	THERMOPLASTIC(LCP)	(UL 94V-0) BLACK
No.	PART NAME	QTY	MATERIAL	REMARK

KEM 奇速科技有限公司
Qi-Speed Technology CO., LTD.

產品名稱:
PRODUCT NAME

HDMI AF FEMALE
正向沉板DIP H2.43mm

料號:KHD17-111XXB-01
PART NUMBER

圖號:KHD17-111XXB-01-1
DRAWING NO

版本: REV. 0

單位: mm	繪圖	設計	審核	核准
比例:	DRAWING	DESIGNED	CHECKED BY	APPROVAL BY
公差: .X ±0.38 .XX ±0.25 .XXX ±0.13	JOHNY	JOHNY	LUKE	JAMES
日期: 2017/8/5				

版本	修改事項	修改日期

