



※ SIGN “(X)” IS IMPORTANCE DIMENSION



PIN	Signal Name	Description	PIN	Signal Name	Description
A1	GN0	Ground return	B12	GN0	Ground return
A2	SSTxp	Positive half of first SuperSpeed TX differential pair	B11	SSRxp	Positive half of first SuperSpeed RX differential pair
A3	SSTxm	Negative half of first SuperSpeed TX differential pair	B10	SSRxm	Negative half of first SuperSpeed RX differential pair
A4	Vbus	Bus Power	B9	Vbus	Bus Power
A5	CC1	Configuration Channel	B8	SRU2	Sideband Use (SRU)
A6	Dn1	Positive half of the USB 2.0 differential pair-Position 1	B7	Dn2	Negative half of the USB 2.0 differential pair-Position 2
A7	Dn1	Negative half of the USB 2.0 differential pair-Position 1	B6	Dp2	Positive half of the USB 2.0 differential pair-Position 2
A8	SRU1	Sideband Use (SRU)	B5	CC2	Configuration Channel
A9	Vbus	Bus Power	B4	Vbus	Bus Power
A10	SSRxm	Negative half of second SuperSpeed RX differential pair	B3	SSTxm	Negative half of second SuperSpeed TX differential pair
A11	SSRxp	Positive half of second SuperSpeed RX differential pair	B2	SSTxp	Positive half of second SuperSpeed TX differential pair
A12	GN0	Ground return	B1	GN0	Ground return



版本: REV. 0

9	密封圈	1PCS	硅胶		
8	胶水	1PCS	硅胶, 黑色		
7	外壳	1PCS	SUS304 , T=0.15. 镀镍50μ" MIN.		
6	内拉伸壳	1PCS	SUS304 , T=0.20. 镀镍50μ" MIN.		
5	EMU拉伸壳	1PCS	SUS304 , T=0.12. 镀镍50μ" MIN.		
4	上排端子	1SET	铜合金, T=0.12. 底层镀镍 50~100μ", 功能接触区单面		
3	下排端子	1SET	刷镀 Au 15μ", 焊接区双面镀金 G/F.		
2	中板	1PCS	SUS301-1/4 H. 镀镍50μ" MIN.		
1	塑胶	1PCS	PA BLACK		
项目	组成部件	用量	材质/处理		备注