



技术参数 SPECIFICATIONS

- 级数: 4~36 Poles: 4~36
- 额定电压: AC, DC, 200V(50HZ有效值)
Voltage rating: AC, DC, 200V(50HZ)
- 额定电流: 0.4A, AC, DC
Current rating: 0.4A, AC, DC
- 耐电压: 200V AC/minute
Withstand voltage: 200V AC/minute
- 工作温度: -25°C~+85°C
Working Temperature: -25°C~+85°C
- 绝缘电阻: $\geq 500\text{M}\Omega$
Insulation resistance: $\geq 500\text{M}\Omega$
- 接触电阻: $\leq 0.02\Omega$
Contact resistance: $\leq 0.02\Omega$
- 双面接触:
Dual Contact

接触件(TERMINAL)

- 材质: 磷铜镀锡
Material: The Lin copper plates tin
- 塑胶本体(Housing)
- 材质: PA9T, UL 94V-0
Material: PA9T, UL 94V-0

PART NO.:

HCO101 - XX 2 L X - (X)

① ② ③ ④

①PIN数 NO. OF CONTACTS 04P~36P

②端子电镀 TERMINAL PLATING:

L: 锡 TIN

③包装方式 PACKING MODE:

3: TUBE

4: TAPE & REEL

④ None : 正针

F: 反针

尺寸 mm P数	DIM.A	DIM.B	DIM.C
4	3.00	5.10	7.00
5	4.00	6.10	8.00
6	5.00	7.10	9.00
7	6.00	8.10	10.00
8	7.00	9.10	11.00
9	8.00	10.10	12.00
10	9.00	11.10	13.00
11	10.00	12.10	14.00
12	11.00	13.10	15.00
13	12.00	14.10	16.00
14	13.00	15.10	17.00
15	14.00	16.10	18.00
16	15.00	17.10	19.00
17	16.00	18.10	20.00
18	17.00	19.10	21.00
19	18.00	20.10	22.00
20	19.00	21.10	23.00
21	20.00	22.10	24.00
22	21.00	23.10	25.00
23	22.00	24.10	26.00
24	23.00	25.10	27.00
25	24.00	26.10	28.00
26	25.00	27.10	29.00
27	26.00	28.10	30.00
28	27.00	29.10	31.00
29	28.00	30.10	32.00
30	29.00	31.10	33.00
31	30.00	32.10	34.00
32	31.00	33.10	35.00
33	32.00	34.10	36.00
34	33.00	35.10	37.00
35	34.00	36.10	38.00
36	35.00	37.10	39.00

KEm 奇速科技有限公司
Qi-Speed Technology CO., LTD.

產品名稱:
PRODUCT NAME

卧式 FPC P:1.0 DIP

版本	修改事項	修改日期

單位: mm		繪圖	設計	審核	核准
比例:		DRAWING	DESIGNED	CHECKED BY	APPROVAL BY
公差: .X ±0.25		JOHNY	JOHNY	LUKE	JAMES
.XX ±0.25					
.XXX ±0.13					
日期: 2023/9/11					

料號:HCO101-XX2LX
PART NUMBER

圖號:HCO101-XX2LX-1
DRAWING NO

版本: REV. 0